



Mastercool[®] Inc.
"World Class Quality"

Rondo d.o.o.
Dalmatinskih Brigada 11, 51211 Matulji
tel +385 51 275 089, fax +385 51 273 567
www.rondodoo.hr , email - info@rondodoo.hr

"MASTERCLEANSE" STROJ ZA ISPIRANJE KLIMA SISTEMA



KARAKTERISTIKE :

- Ventili od nehrđajućeg celika
- 1/4" SAE spojnice
- Mogućnost dodavanja vanjskog rezervoara
- Spajanje na vanjsku bocu sa dušikom
- Pumpa opremljena sa mehaničkim brtvilom i PTFE brtvom
- Mehanički filter je ugrađen na usisu

SPECIFIKACIJE :

- PROTOK: 4 g/min (16 l/min)
- MOTOR PUMPE - 0.75 kW
- REZERVOARI : 10 l
- CRIJEVA: 3 m
- DIMENZIJA: (381 mm (D) x 406 mm (Š) x 609 mm (V) / sa produženom ručkom 914 mm (h))
- TEŽINA: 19 kg

ZAŠTO MASTERCLEANSE - jer ne koristi skupe i opasne plinove za ispiranje već specijalne tekućine i dušik sa kojima se postiže neusporedivo bolji rezultati .

Mastercool Vam predstavlja kompletno rješenje za ispiranje prljavštine i ostalih stranih predmeta iz klima sistema na vozilima . Jednostavno i profesionalno rješenje bez demontaže komponentana sa vozila . Ispiranje sa specijalnim brzo isparavajućim tekućinama koje sakupljaju svu prljavštinu i nečistoće .

Spojite stroj na vozilo , montirate Mastercool ventil na vozilo i proces kreće , nemože jednostavnije od ovoga !!!

69900-220
220-240 V / 50/60 Hz

69901-220
220-240 V / 50/60 Hz

sa integriranim regulatorom tlaka za boce dušika
(za standardne evropske 1 litra boce sa dušikom)

OPCIJA

Mastercool 69925
Multifunkcionalni set za ispiranje
i test curenja za 80% vozila na
tržištu





OPTIONAL ACCESSORIES FOR USE WITH "MASTERCLEANSE" FLUSH MACHINE

**69925
MULTIPLE FLUSHING & LEAK TEST ADAPTER KIT
FOR FLUSH MACHINE**

Multi-purpose leak test and flushing adapters suitable for more than 80% of the automotive air conditioning systems in the market!



**91092-A
FLUSH GUN**



NITROGEN PRESSURE REGULATORS

Mastercool's nitrogen regulator is specifically designed to meet the specifications of HVAC/R and automotive A/C systems. This single stage nitrogen regulator is used to test systems for leaks when they do not contain refrigerant.

- 1/4" SAE flare outlet port, with control valve, to keep pressure on the regulator at all times
- T-Handle for ease of pressure adjustment
- 63 mm (2 1/2") gauges with guards
- High pressure gauge 4400 psig (300 bar), Low pressure gauge 1000 psig (70 bar)

Model #	53001	53002	53003	53004	53005
Standard	CGA580 (US)	DIN477#6 and DIN477#10 (This unit includes an adapter to convert DIN477#6 to DIN477#10) (France/Germany)	BS3 (England)	AS2473.2 (Australia)	5-UNI11144 (Italy)

1/4 FL-M outlet connection

PRESSURE TESTING REGULATOR KITS



53010 PRESSURE TESTING REGULATOR KIT (US)

53001 Nitrogen Pressure Regulator, 48" Yellow Charging Hose (47482), Leak Testing Adapter (53042), Blow molded case (53000-PB)

53020 PRESSURE TESTING REGULATOR KIT (France/Germany)

53002 Nitrogen Pressure Regulator, 48" Yellow Charging Hose (47482), Leak Testing Adapter (53042), R410a Straight Adapter 1/4 FL-M x 5/16 Swivel-F (90413), Blow molded case (53000-PB)

53030 PRESSURE TESTING REGULATOR KIT (England)

53003 Nitrogen Pressure Regulator, 48" Yellow Charging Hose (47482), Leak Testing Adapter (53042), R410a Straight Adapter 1/4 FL-M x 5/16 Swivel-F (90413), Blow molded case (53000-PB)

53040 PRESSURE TESTING REGULATOR KIT (Australia)

53004 Nitrogen Pressure Regulator, 48" Yellow Charging Hose (47482), Leak Testing Adapter (53042), Blow molded case (53000-PB)

53050 PRESSURE TESTING REGULATOR KIT (Italy)

53005 Nitrogen Pressure Regulator, 48" Yellow Charging Hose (47482), Leak Testing Adapter (53042), Blow molded case (53000-PB)